

TECHNICAL INFORMATION

Tamturbo® Touch-Free™ Compressors

Touch-Free. Oil-Free. Care-Free.

PRESSURE RANGE 5–9 BAR (75–130 PSI)

| Model | Working pressure | | Free air delivery | | Input power | | Nominal power | | Dimensions (Width / Length / Height) | | Sound level dB(A) | Cooling |
|----------|------------------|--------|---------------------|----------|-------------|---------|---------------|-----|---|----------------------|----------------------|---------|
| | bar | psi | m ³ /min | cfm | kW | hp | kW | hp | mm | inch | | |
| TT145 MR | 5–9 | 75–130 | 8.0–20.2 | 290–720 | 54–199 | 72–267 | 145 | 195 | 1821 2173 2059 | 71.7 85.6 81.1 | 76 | Liquid |
| TT145 HR | 5–9 | 75–130 | 12.8–28.0 | 460–990 | 54–199 | 72–267 | 145 | 195 | 1821 2173 2059 | 71.7 85.6 81.1 | 76 | Liquid |
| TT185 | 5–9 | 75–130 | 14.2–33.0 | 510–1170 | 81–236 | 109–316 | 185 | 250 | 1821 2173 2059 | 71.7 85.6 81.1 | 76 | Liquid |
| TT265 | 5–9 | 75–130 | 20.5–37.6 | 730–1330 | 131–256 | 176–343 | 265 | 355 | 2489 2021 2022 | 98.0 79.6 79.6 | 76 | Liquid |
| TT305 | 5–9 | 75–130 | 20.5–45.8 | 720–1620 | 129–351 | 173–470 | 305 | 410 | 2489 2021 2022 | 98.0 79.6 79.6 | 76 | Liquid |
| TT325 | 5–8 | 75–115 | 22.5–53.3 | 800–1890 | 129–351 | 173–470 | 325 | 435 | 2489 2021 2022 | 98.0 79.6 79.6 | 76 | Liquid |

PRESSURE RANGE 2–5 BAR (30–75PSI)

| Model | Working pressure | | Free air delivery | | Input power | | Nominal power | | Dimensions (Width / Length / Height) | | Sound level dB(A) | Cooling |
|----------|------------------|-------|---------------------|----------|-------------|--------|---------------|-----|---|----------------------|----------------------|---------|
| | bar | psi | m ³ /min | cfm | kW | hp | kW | hp | mm | inch | | |
| TT115 MR | 2–5 | 30–75 | 6.6–20.3 | 240–720 | 30–145 | 41–194 | 115 | 155 | 1821 2173 2059 | 71.7 85.6 81.1 | 76 | Liquid |
| TT115 HR | 2–5 | 30–75 | 10.4–28.1 | 370–1000 | 30–145 | 41–194 | 115 | 155 | 1821 2173 2059 | 71.7 85.6 81.1 | 76 | Liquid |
| TT135 | 2–4.5 | 30–65 | 12.2–33.0 | 440–1170 | 47–155 | 63–207 | 135 | 180 | 1821 2173 2059 | 71.7 85.6 81.1 | 76 | Liquid |

Tamturbo
JUST AIR

Tel +1 (314) 576-9001 Americas
Tel +358 (0)10 423 2303 Global
info@tamturbo.com
www.tamturbo.com



ENERGY RECOVERY – STANDARD FEATURE

Cooling liquid outlet temperature* 15–65°C (60–150°F)
*with BHR up to 90°C (194°F)
Cooling liquid inlet temperature 5–35°C (40–95°F)
Ambient and inlet air temperature 5–40°C (40–105°F)